



Figure 1: TV with Enseo STB cable connection diagram.

Enseo Set Top Box

What You Will Need:

- TA-7650 or TA-7650/TA-7500L
 - MediaHub HD Connectivity Panel
 - Power Supply Cable (*Note: MediaHub with Power/Data Extender model includes TWO power supplies – one for media panel and one for power panel*)
 - Ethernet Cable (for MediaHub with Power/Data Extender model only)
- Cable Kit
 - HDMI Cable (3m)
 - RS-232 Cable
 - DB9-3.5mm Adapter
 - CAB-40583D5H Cable (Control Cable needed for HD2000 STB only)
- Enseo STB and remote control
- Enseo STB Cable Kit (RJ11 Data cable and HDMI cable)
- Hospitality TV

TV + Enseo STB Installation

For Enseo HD3000 STB firmware v.2.12.04+

For Enseo HD2000 STB firmware v.2.10.29.17+

MediaHub HD DIP Mode 52: DWN-UP-DWN-UP -- DWN-DWN-UP-DWN

MediaHub HD Firmware Version: 1.23+

MediaHub HD Video Driver Firmware: 3.26+

Configure Enseo STB: Press <Channel Up>, <Right Arrow>, <Left Arrow>, <MUTE> to enter set-up screen. Go to Control Options and AUX panel. Set BAUD Rate to 9600.

Follow basic cable connection diagram illustrated in Figure 1. See model-specific connections and TV configuration requirements according to the TV make/model below.

Any Samsung North America Model + Enseo HD2000/3000

Connect STB RJ11 to TV's DATA port using Samsung's BN3900865B RJ11 cable.

Configure TV: Using Samsung remote control, enter the MENU by pressing <INFO>, <MENU>, <0>, <1>, <EXIT>, Ensure the following is selected:

Hotel Mode = ON

RJP HDMI Option = HDMI2

Set SI Vendor to ENSEO.

Panasonic North America Series 20/12 + Enseio HD2000/3000

Configure TV: Go into HOTEL MODE (using Panasonic remote, press <MENU>, <G>, <Y>, <0>), select the following:

MODE = ON

TA Control = EXTERNAL

BUTTON LOCK = OFF

Philips North America, LG North America, Sharp North America + Enseio HD2000/3000

No TV configuration needed.