



Figure 1: Cable connection diagram for installing MediaHub HD to a LodgeNet STB using the PCD.

If the TV has an internal LodgeNet terminal card, connect the GAME/DATA Cable to the TV's DATA port.

Note: Dotted cables in diagram are packaged with PCD solid black cables are packaged with MediaHub HD.

LodgeNet PPV System (with ANY TV)

Installing MediaHub HD to auto-switch a TV in a LodgeNet environment requires a TeleAdapt Protocol Converter Dongle (PCD), part number TA-8700-A01.

What You Will Need:

- TA-7650 or TA-7650/TA-7500L
MediaHub HD Connectivity Panel
Power Supply Cable (*Note: MediaHub with Power/Data Extender model includes TWO power supplies – one for media panel and one for power panel*)
Ethernet Cable (for MediaHub with Power/Data Extender model only)
- MediaHub Cable Kit
HDMI Cable (3m)
- PCD – TA-8700-A01
Protocol Converter Dongle
Game/Data Cable (RJ11-RJ11) CAB-0505D60
MediaHub Cable (DB9-RJ11) CAB-0502D60
- Hospitality TV with internal LodgeNet terminal with remote control and/or LodgeNet STB with remote control

For hospitality displays connected to a LodgeNet PPV/VOD System*

To install MediaHub HD and PCD in a LodgeNet environment, follow the cable connection diagram in Figure 1 to the left.

MediaHub DIP Mode B0: UP-DWN-UP-UP DWN-DWN-DWN-DWN

PCD DIP Mode: UP-DWN

Configure TV as recommended by your VOD provider. No other configuration needed.

*Note: PCD does not support legacy OnCommand (OCV) STB.