

Special Notes:

For legacy OnCommand STBs (OCV), please refer to the TV-specific installation instructions. Only certain TV model serial connections support auto-switching MediaHub SL+ in an OCV environment.

The ASM Installation Kit contains an RJ12 male-to-male control cable. Use this cable for the Game/Data connection.

If your hospitality TV has a built-in LodgeNet terminal (internal terminal card), plug the Game/Data cable into the TV's DATA port.

To use the charging feature of iDock, make sure to connect the USB Power Supply to a wall outlet.

Be sure the ASM DIP Switches are set to the appropriate positions:

TV/VOD	SW 1	SW 2	SW 3	SW 4
LODGENET	OFF	OFF	OFF	OFF
TELEADAPT	ON	OFF	OFF	OFF
SAMSUNG (OPTIONAL)	OFF	ON	OFF	OFF
LG/RJP	ON	ON	OFF	OFF
PHILIPS	OFF	OFF	ON	OFF
ENSEO	ON	OFF	ON	OFF
PANASONIC	OFF	ON	ON	OFF
SONY	ON	ON	ON	OFF
SHARP	OFF	OFF	OFF	ON
HISENSE	ON	OFF	OFF	ON

LodgeNet PPV Systems (with ANY TV)

Follow the cable connection diagram below.

ASM DIP Mode: DWN-DWN-DWN-DWN

Configure TV Menu Settings as recommended by your VOD provider.

