

Special Notes:

For legacy OnCommand STBs (OCV), please refer to the TV-specific installation instructions. Only certain TV model serial connections support auto-switching MediaHub SL⁺ in an OCV environment.

The ASM Installation Kit contains an RJ12 male-to-male control cable. Use this cable for the Game/Data connection.

If your hospitality TV has a built-in LodgeNet terminal (internal terminal card), plug the Game/Data cable into the TV's DATA port.

The Game/Data port draws enough power for the ASM. Therefore, no need to connect the ASM's USB Power In.

Be sure the ASM DIP Switches are set to the appropriate positions:

TV/VOD	SW 1	SW 2	SW 3	SW 4
LODGENET	OFF	OFF	OFF	OFF
TELEADAPT	ON	OFF	OFF	OFF
SAMSUNG (OPTIONAL)	OFF	ON	OFF	OFF
LG / RJP	ON	ON	OFF	OFF
PHILIPS	OFF	OFF	ON	OFF
ENSEO	ON	OFF	ON	OFF
PANASONIC	OFF	ON	ON	OFF
SONY	ON	ON	ON	OFF
SHARP	OFF	OFF	OFF	ON
HISENSE	ON	OFF	OFF	ON

LodgeNet PPV Systems (with ANY TV)

- 1 | Ensure the DIP Switch Settings on ASM are in the appropriate positions according to the installation choices below.
- 2 | Connect the cables between the MediaHub SL, ASM and TV and STB according to schematic shown for your installation choice.
- 3 | Plug the power supply into a wall power socket using the correct plug for your country.
- 4 | Power ON the TV and configure the TV settings according to the model-specific requirements below.
- 5 | After all menu settings and AV connections are done, power cycle the TV to lock in settings.

Follow the cable connection diagram below.

ASM DIP Mode: DWN-DWN-DWN-DWN

Configure TV Menu Settings as recommended by your VOD provider.

